



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)

MCX MARKETING SDN. BHD. (Co. No. 363532-T)

H. Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.

Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919

KL. Office : No. 4, Jalan TPP 5/10, Taman Perindustrian Puchong, 47100 Puchong, Selangor.

Tel : (60 3) 8060 0370 / 8060 0372 Fax : (60 3) 8060 0723

Email : info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal® 500°F BLUE RTV SILICONE SEALANT

1. Product & Company Identification

1.1 Product Detail

Product name: **xtraseal® 500°F Blue RTV Silicone Sealant**
Physical form: **Paste**
Odour: **Acetic Acid**
Colour: **Blue**
CAS No.: **Mixture**

1.2 Company Details:

Manufacturer: **Mohm Chemical Sdn Bhd**
Address: **No. 32 (Lot 1617), Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.**
Tel: **+ 60-7-3331222**
Fax: **+ 60-7-3320545/ +60-7-3337919**

2. Composition/ Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Approx WT%</u>
Methyltriacetoxysilane	4253-34-3	1-5%
Amorphous fumed silica	11294-55-25	10-30%
Dimethyl siloxane, Hydroxy-terminated	70131-67-8	60-80%

3. Hazards Identification

Ingestion: **Irritation of the mouth, throat and stomach.**
Skin contact: **Uncured product contact will irritate lips, gums and tongue. Uncured product contact may irritate the skin.**
Inhalation: **May cause mild respiratory irritation.**
Eye contact: **Uncured product contact irritates eyes.**

4. First-aid Measures

Take off all contaminated clothing immediately.
In case of ingestion: **Seek medical advice immediately.**
In case of skin contact: **Wipe with paper towel and immediately clean with water and soap.**
In case of eyes contact: **Immediately flush with water, seek medical advice if necessary.**

5. Fire Fighting Measures

Suitable extinguishing media: **All standard fire-fighting media.**
Unsuitable extinguishing media: **Unknown**
Hazardous decomposition: **Carbon dioxide, carbon monoxide, silicone dioxide and acetic acid.**



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)
MCX MARKETING SDN. BHD. (Co. No. 363532-T)
H. Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
KL.Office : No. 4, Jalan TPP 5/10, Taman Perindustrian Puchong, 47100 Puchong, Selangor.
Tel : (60 3) 8060 0370 / 8060 0372 Fax : (60 3) 8060 0723
Email : info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

x'traseal® 500°F BLUE RTV SILICONE SEALANT

6. Accidental release measures

Methods for cleaning up: Take up mechanically.

7. Handling and Storage

Handling: Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety shoes.
Protection against fire/ explosion: General rules of fire prevention should be observed.
Storage: Keep container tightly closed and dry.
Cautions: Extreme heavy in drum form if product packed in 200L drum.

8. Exposure control/ Personal protection

Ingredients with limited values to be controlled: Not indicated.
Local exhaust: recommended
General ventilation: recommended
Hand protection: Suitable protective gloves.
Eye protection: Safety/ protective glasses.
Flammability: Combustible

9. Physical and Chemical Properties

Form: Paste
Specific gravity: 1.07
Colour: Blue
Viscosity: Not indicated.
Odour: Acetic Acid.
%Volatile by volume (25°C): < 3.9%
Boiling point: Not Applicable.
Flash point: Not Applicable.
Ignition temperature: Not Applicable.
Vapour pressure: 15hPa (acetic acid).
Solubility in water (20°C) Insoluble
Solubility in organic solvent: Toluene.

Note: the above information is not intended for use in preparing specification.



MATERIAL SAFETY DATA SHEET

xtraseal® 500°F BLUE RTV SILICONE SEALANT

10. Stability and Reactivity

Chemical stability:	Decomposition at temperature above 250°C
Incompatibility (material to be avoid):	None known.
Conditions to be avoid:	None known.
Dangerous reactions:	None known.
Dangerous products of decomposition:	Acetic acid during curing.
In case of fire, carbon dioxide, carbon monoxide, silicone dioxide and acetic acid.	

11. Toxicological Information

Acute toxicity:	Not determined
Primary irritant effect, On the skin:	Irritant for skin and mucous membranes.
On the eye:	Irritant effect
Sensitization:	Sensitization possible by inhalation.
Additional Toxicological information:	When used and handled according to specification, the product does not have any harmful effects according to our experience and the information provided to us.

12. Ecological Information

Complete information not yet available.

13. Disposal considerations

For cured sealant landfill may be suitable.
With respect to local regulation, dispose of to suitable incineration plant.

14. Transport Information

Proper shipping name:	Silicone Sealant
Hazard technical name:	Not available.
Hazard class:	Not available.
No dangerous goods under the transport regulation.	

15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements.



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)

MCX MARKETING SDN. BHD. (Co. No. 363532-T)

H. Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.

Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919

KL. Office : No. 4, Jalan TPP 5/10, Taman Perindustrian Puchong, 47100 Puchong, Selangor.

Tel : (60 3) 8060 0370 / 8060 0372 Fax : (60 3) 8060 0723

Email : info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

x'traseal[®] 500°F BLUE RTV SILICONE SEALANT

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of MSDS ***