



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)

MCX MARKETING SDN. BHD. (Co. No. 363532-T)

H. Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.

Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919

KL.Office : No. 4, Jalan TPP 5/10, Taman Perindustrian Puchong, 47100 Puchong, Selangor.

Tel : (60 3) 8060 0370 / 8060 0372 Fax : (60 3) 8060 0723

Email : info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

x'traseal® BT-390 WINDSCREEN SEALANT

1. Product & Company Identification

1.1 Product Detail

Product name: x'traseal® BT-390 Windscreen Sealant
Physical form: Extruded solid putty tape
Odour: Odourless
CAS No.: Mixture
Flammability: Very low

1.2 Company Details:

Manufacturer: Mohm Chemical Sdn Bhd
Address: No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel: + 60-7-3331222
Fax: + 60-7-3320545/ + 60-7-3337919

2. Composition/ Hazardous Components

| <u>Chemical Name</u> | <u>Hazard</u> |
|----------------------|----------------------|
| Synthetic Rubber | None currently known |

3. Hazards Identification

Ingestion: No significant health hazards identified
Skin contact: No significant health hazards identified. Hot material can cause thermal burns.
Inhalation: No significant health hazards identified.
Eye contact: No significant health hazards identified. Hot material can cause thermal burns.

4. First-aid Measures

In case of swallowed If large amount is swallowed, get medical attention
In case of inhalation If adverse effects occur, remove to uncontaminated area. Get good medical attention.
In case of skin contact: Wash exposed skin with hand cleaner / soap & water. Cool with water for at least 15 minutes if hot material is used.
In case of eyes contact: Flush eyes with plenty of clean running tap water for at least 15 minutes
Advice to doctor: Treat symptomatically.



MATERIAL SAFETY DATA SHEET

x'traseal® BT-390 WINDSCREEN SEALANT

5. Fire Fighting Measures

| | |
|-------------------------------|---|
| Flammability: | Very Low |
| Suitable extinguishing media: | Dry Chemical, Foam, CO ² , Water Fog |
| Flash Point | Minimum 180 °C |

6. Accidental release measures

| | |
|----------|---|
| Methods: | Exclude sources of ignition and ventilation the area Exclude non-essential personnel. Avoid breathing vapour |
|----------|---|

7. Handling and Storage

| | |
|-------------------------------------|--|
| Handling: | Ensure good ventilation during processing. Wear safety shoes. |
| Protection against fire/ explosion: | General rules of fire prevention should be observed. |
| Storage: | Keep in a cool shaded place, away from heat & direct sunlight. |

8. Exposure control/ Personal protection

| | |
|------------------|-----------------------------|
| Hand protection: | Suitable protective gloves. |
| Eye protection: | Safety / Protective Goggles |

9. Physical and Chemical Properties

| | |
|-------------------------|---------------------------|
| Form: | Extruded solid putty tape |
| Specific gravity: | 1.3 ± 0.1 |
| Colour: | Black |
| Odour: | Odourless |
| Melting Temperature | Not Applicable |
| Boiling point: | Not Applicable |
| Flash point: | Minimum 180 °C |
| Freezing Point | Not Applicable |
| Ignition Temperature: | Non known |
| Vapour Pressure (25°C) | Non known |
| Soluble in Water (25°C) | Negligible, below 0-1% |

Note: the above information is not intended for use in preparing specification.



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)

MCX MARKETING SDN. BHD. (Co. No. 363532-T)

H. Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.

Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919

KL. Office : No. 4, Jalan TPP 5/10, Taman Perindustrian Puchong, 47100 Puchong, Selangor.

Tel : (60 3) 8060 0370 / 8060 0372 Fax : (60 3) 8060 0723

Email : info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

x'traseal® BT-390 WINDSCREEN SEALANT

10. Stability and Reactivity

| | |
|----------------------------------|--|
| Hazardous Decomposition Products | Incomplete burning can produce CO, CO ² , and other harmful products. |
| Hazardous Reaction | No dangerous reaction known |

11. Toxicological Information

| | |
|--------------|-------------------------|
| On the skin: | May cause sensitization |
| On the eye: | Possibility irritating |

12. Ecological Information

Large quantities of products should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface water.

13. Disposal considerations

Do not allow large quantities to enter the drains or watercourses or dispose of where ground surface may be affected. Residue in emptied containers should be covered and should be disposed of in accordance with regulations made under the control of Pollution & Environment Protection Acts.

14. Transport Information

Not Available

15. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of MSDS ***