



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)
MCX MARKETING SDN. BHD. (Co. No. 363532-T)
H. Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
KL. Office : No. 4, Jalan TPP 5/10, Taman Perindustrian Puchong, 47100 Puchong, Selangor.
Tel : (60 3) 8060 0370 / 8060 0372 Fax : (60 3) 8060 0723
Email : info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

x'traseal® DYNASOL METAL POLISH

1. Product & Company Identification

1.1 Product Detail

Product name: **x'traseal® DYNASOL Metal Polish**
Chemical Family: **Complex Mixture**
CAS No.: **Mixture**

1.2 Company Details:

Manufacturer: **Mohm Chemical Sdn Bhd**
Address: **No. 32 (Lot 1617), Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.**
Tel: **+ 60-7-3331222**
Fax: **+ 60-7-3320545/ + 60-7-3337919**

2. Components Of Mixture

The precise composition of this mixture is proprietary information.

Contains: Water, solvent, non-abrasive polishing powders, carnauba wax, microcrystalline wax, emulsifiers, and surfactants.

3. Health/ First Aid Information

First Aid And Nature Of Hazard:

Eye Contact : May cause eye irritation. Direct contact with liquid may cause irritation and redness. Flush eyes immediately with water.

Skin Contact : May cause mild skin irritation. Prolonged or repeated contact may cause dermatitis. Wash exposed portions of the skin with soap and water.

Inhalation : This material is expected to have a low degree of toxicity by inhalation. Intentional misuse by deliberately concentrating and inhaling this product may be harmful. Inhalation of vapors (generated at high temperatures only) from this product may cause mild irritation of the upper respiratory tract. Remove person to fresh air.

Ingestion : Seek medical attention immediately. Do not induce vomiting unless directed by a physician. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. May cause gastrointestinal irritation.



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)
MCX MARKETING SDN. BHD. (Co. No. 363532-T)
H. Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
KL. Office : No. 4, Jalan TPP 5/10, Taman Perindustrian Puchong, 47100 Puchong, Selangor.
Tel : (60 3) 8060 0370 / 8060 0372 Fax : (60 3) 8060 0723
Email : info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

x'traseal[®] DYNASOL METAL POLISH

4. Fire Protection

Flash Point:	Not applicable.
Handling Precautions:	Keep product away from ignition sources such as heat and open flames. Store in a cool place under shade.
Unusual Fire and Explosion Hazards:	None.

5. Physical Data

Non-flammable	
Solubility in water:	Slightly dispersible
Appearance:	White paste
Specific Gravity:	1.20 (at 25°C)

6. Environmental Protection

Waste Disposal Method:	All disposals must comply with relevant authorities' regulations.
Procedures in Case of Leakage:	Floor may be slippery; use caution to avoid falling. May burn although not readily ignitable. Use cautious judgment when cleaning up large spills. Provide adequate ventilation during clean-up.

7. Other Information

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use. Buyer assumes all such risks.

*** End Of MSDS ***