



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)
MCX MARKETING SDN. BHD. (Co. No. 363532-T)
H. Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
KL. Office : No. 4, Jalan TPP 5/10, Taman Perindustrian Puchong, 47100 Puchong, Selangor.
Tel : (60 3) 8060 0370 / 8060 0372 Fax : (60 3) 8060 0723
Email : info@mochem.com Website: www.mochem.com / www.xtraseal.com

TECHNICAL DATA SHEET

x'traseal[®] CONTACT ADHESIVE

DESCRIPTION:

x'traseal[®] CONTACT ADHESIVE DRIES TO FORM A FLEXIBLE AND WATER RESISTANT BOND ON MOST OF THE SURFACE. THE ADHESIVE CAN BE USE TO BOND WOOD, PAPER, MOST OF THE PLASTICS, TILE, PVC LEATHER, GLASS, FABRIC AND RUBBER.

FEATURES:

- ◆ EASY TO APPLY.
- ◆ STRONG BONDING STRENGTH.
- ◆ WATER RESISTANT.
- ◆ COST SAVING.
- ◆ REMAIN FLEXIBLE WHEN DRIED.

USES:

A GENERAL PURPOSE ADHESIVE FOR FURNITURE AND HOME DIY PROJECT. BONDING OF WOOD, SPONGE, FORMICA, PVC CARPET, METAL, CLOTH AND PAPER PRODUCTS.

LIMITATIONS:

NOT USE FOR: IN AREAS OF CONSTANT WATER IMMERSION.
NOT FOR: PE, PP, PTFE AND BITUMINOUS SURFACE.

APPLICATION:

- ◆ SURFACE MUST BE CLEAN, DRY AND FREE FROM GREASE.
- ◆ MASK SMOOTH SURFACE TO SIMPLIFY CLEAN UP.
- ◆ APPLY TO BOTH SURFACES EVENLY.
- ◆ FOR ABSORBENT OR POROUS SURFACES, NORMALLY TWO COATS ARE RECOMMENDED.
- ◆ APPLY SUITABLE PRESSURE ON BONDING SUBSTRATES.
- ◆ CLEAN OFF EXCESS ADHESIVE WITH TOLUENE.

CURING TIME:

CONTACT ADHESIVE WILL BOND IN APPROXIMATELY 30 - 45 MINUTES UNDER ROOM TEMPERATURE.
THE CURING TIME WILL BE LONGER FOR SMOOTH SURFACES.

SPECIFICATION:

APPEARANCE	LIGHT BROWN LIQUID.
ODOUR	AROMATIC ODOUR.
SPECIFIC GRAVITY	0.90±0.03
VISCOSITY(S4, 50RPM)	4,000 CPS
APPLICATION TEMP.	-10°C TO 40°C
SERVICE TEMPERATURE	-10°C TO 60°C
SHELF LIFE	12 MONTHS



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)

MCX MARKETING SDN. BHD. (Co. No. 363532-T)

H. Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.

Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919

KL. Office : No. 4, Jalan TPP 5/10, Taman Perindustrian Puchong, 47100 Puchong, Selangor.

Tel : (60 3) 8060 0370 / 8060 0372 Fax : (60 3) 8060 0723

Email : info@mochem.com Website: www.mochem.com / www.xtraseal.com

TECHNICAL DATA SHEET

x'traseal[®] CONTACT ADHESIVE

CAUTION:

UNCURED ADHESIVE MAY CAUSE SKIN, EYE AND RESPIRATORY SYSTEM IRRITATION.

USE ONLY IN WELL VENTILATED AREAS.

USE APPROPRIATE PERSONAL PROTECTION TO AVOID CONTACT WITH SKIN AND EYES.

IN CASE OF EYE CONTACT OR IRRITATION, FLUSH EYE IMMEDIATELY WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION.

IN CASE OF SKIN CONTACT, WASH AFFECTED AREAS WITH HAND CLEANER FOLLOWED BY SOAP AND WATER.

FOR FURTHER HEALTH AND SAFETY INFORMATION CONSULT THE CURRENT MATERIAL SAFETY DATA SHEET.