



**MOHM CHEMICAL SDN. BHD.** (Co. No. 275851-U)

**MCX MARKETING SDN. BHD.** (Co. No. 363532-T)

H.Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.

Tel: (60) 7 333 1222 Fax: (60) 7 332 0545/ 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,  
40400 Shah Alam, Selangor, Malaysia.

Tel: (60) 3 5124 0876/ 5124 0878 Fax: (60) 3 5124 0877

Email: info@mochem.com Website: www.mochem.com/ www.xtraseal.com

## MATERIAL SAFETY DATA SHEET

### x'traseal® BT-330 INSTANT FLASHING TAPE

#### 1. Product & Company Identification

##### 1.1 Product Detail

Product name: **x'traseal®** BT-330 Instant Flashing Tape

##### 1.2 Company Details:

Manufacturer: Mohm Chemical Sdn Bhd

Address: No. 32 (Lot 1617), Jalan Temenggong, Off Jalan Tampoi, 81100  
Johor Bahru, Johor, Malaysia.

Tel: + 60-7-3331222

Fax: + 60-7-3320545/ + 60-7-3337919

#### 2. Composition/ Hazardous Components

Composite Comments: Aluminium foil, Rubber modified bitumen adhesive, P.E release film

#### 3. Hazards Identification

This Product is not classified as hazardous under current regulations.

#### 4. First-aid Measures

**Inhalation:** Move the exposed person to fresh air at once. Provide fresh air, warmth and rest. Preferably in a comfortable upright sitting position. Get medical attention if any discomfort continues.

**Ingestion:** Do not induce vomiting, never make unconscious person vomit or drunk fluids! Rinse mouth thoroughly. Promptly get affected personal to drink large volumes of water to dilute the swallowed chemical. Obtain medical advise provide rest, warmth and fresh air.

**Skin:** Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation develops.

**Eyes:** Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.



**MOHM CHEMICAL SDN. BHD.** (Co. No. 275851-U)

**MCX MARKETING SDN. BHD.** (Co. No. 363532-T)

H.Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.

Tel: (60) 7 333 1222 Fax: (60) 7 332 0545/ 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,  
40400 Shah Alam, Selangor, Malaysia.

Tel: (60) 3 5124 0876/ 5124 0878 Fax: (60) 3 5124 0877

Email: info@mochem.com Website: www.mochem.com/ www.xtraseal.com

## MATERIAL SAFETY DATA SHEET

### xtraseal® BT-330 INSTANT FLASHING TAPE

#### 5. Fire Fighting Measures

**Extinguishing Media:** This material is not flammable, use extinguishing media appropriate for surrounding fire.

#### 6. Accidental release measures

**Precautions to protect environment.**

Avoid suboil penetration. Prevent product from entering drains. Do not contaminate surface water.

**Spill Cleanup Methods:** N/A.

#### 7. Handling and Storage

**Usage Precautions:** Avoid handling which leads to dust formation. Provide good ventilation.

**Store Precautions:** Store moderate temperature at 5°C - 40°C in dry, well ventilated area.

#### 8. Exposure control/ Personal protection

**Ventilation:** Provide adequate general and local exhaust ventilation.  
**Protective Globes:** No specific hand protection noted. But gloves may be advisable. For prolonged or repeated skin contact use suitable protective gloves. Rubber or plastics.  
**Eye Protection:** Wear safety goggles where there is danger of eye contact.  
**Other Protection :** Wear appropriate clothing to prevent repeated or prolonged skin contact. Provide eye wash station.

#### 9. Physical and Chemical Properties

**Appearance:** Metallic looking foil  
**Colour:** N/A  
**Odours/ Taste:** Bituminous  
**Solubility Description:** Insoluble in water.



**MOHM CHEMICAL SDN. BHD.** (Co. No. 275851-U)

**MCX MARKETING SDN. BHD.** (Co. No. 363532-T)

H.Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.

Tel: (60) 7 333 1222 Fax: (60) 7 332 0545/ 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,  
40400 Shah Alam, Selangor, Malaysia.

Tel: (60) 3 5124 0876/ 5124 0878 Fax: (60) 3 5124 0877

Email: info@mochem.com Website: www.mochem.com/ www.xtraseal.com

## MATERIAL SAFETY DATA SHEET

### xtraseal® BT-330 INSTANT FLASHING TAPE

#### 10. Stability and Reactivity

Stability:	Normally Stable
Conditions to be avoid:	N/A
Materials To Avoid:	Strong oxidizing agents, oils, water and any materials which can weaken the adhesiveness of flashing tape.
Hazardous Decomposition Products:	Fire or high temperature create: Asphyxiating gases/ vapours/ fumes of: Carbon dioxide (Co2), Carbon monoxide (CO)

#### 11. Toxicological Information

Inhalation:	Dust may irritate respiratory system or lungs. May cause discomfort if swallowed. Swallowing concentrated chemical may cause severe internal injury. Ingestion may result in perforation of the oesophagus, vomiting, blood, diarrhoea, shock, haemolysis and haemoglobinuria
Ingestion:	
Skin:	Powder may irritate skin
Eyes:	Particles in the eyes because of abrasive action may cause irritation and smarting.
Health Warning:	No specific health warning noted.

#### 12. Ecological Information

Environmental Hazards:	Not regarded as dangerous for the environment
------------------------	---

#### 13. Disposal considerations

Disposal Methods:	Recover and reclaim or recycle, if practical. Dispose on site landfill area. Dispose of in accordance with Local Authority requirements.
-------------------	--



**MOHM CHEMICAL SDN. BHD.** (Co. No. 275851-U)

**MCX MARKETING SDN. BHD.** (Co. No. 363532-T)

H.Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.

Tel: (60) 7 333 1222 Fax: (60) 7 332 0545/ 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,  
40400 Shah Alam, Selangor, Malaysia.

Tel: (60) 3 5124 0876/ 5124 0878 Fax: (60) 3 5124 0877

Email: info@mochem.com Website: www.mochem.com/ www.xrtraseal.com

## MATERIAL SAFETY DATA SHEET

### x® BT-330 INSTANT FLASHING TAPE

#### 14. Transport Information

##### Road

Hazard class: Not classified for transportation  
Road Transport Noted: Not classified for road transportation

##### Rail

Road Transport Noted: Not classified for rail transportation

Sea Transport Noted: Not classified for sea transportation

##### Air

Air Transport Noted: Not classified for air transportation

#### 15. Regulatory Information

Risk Phrases: Not classified  
Safety Phrases: This product is not classified as hazardous under the current ship or carriage regulations, however with all chemical products appropriate not classified.

#### 16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

\*\*\* End Of MSDS \*\*\*