



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)



H.Q. : No.32,Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
 Tel : (60 7) 333 1222 Fax: (60 7) 332 0545 / 333 7919
 Branch : No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
 47100 Shah Alam, Selangor. Malaysia.
 Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
 Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal® BT-390 WINDSCREEN SEALANT

1. Product & Company Identification

1.1 Product Detail	
Product name:	BT-390 Windscreen Sealant
Physical form:	Extruded solid putty tape
Odour:	Odourless
CAS No.:	Mixture
Flammability:	Very low
1.2 Company Details:	
Manufacturer:	Mohm Chemical Sdn Bhd
Address:	No. 32 (Lot 1617), Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel:	+ 60-7-3331222
Fax:	+ 60-7-3320545/ + 60-7-3337919

2. Composition/ Hazardous Components

<u>Chemical Name</u>	<u>Hazard</u>
Synthetic Rubber	Non currently known

3. Hazards Identification

Ingestion:	No significant health hazards identified
Skin contact:	No significant health hazards identified. Hot material can cause thermal burns.
Inhalation:	No significant health hazards identified.
Eye contact:	No significant health hazards identified. Hot material can cause thermal burns.

4. First-aid Measures

In case of swallowed	If large amount is swallowed, get medical attention
In case of inhalation	If adverse effects occur, remove to uncontaminated area. Get good medical attention.
In case of skin contact:	Wash exposed skin with hand cleaner / soap & water. Cool with water for at least 15 minutes if hot material is used.
In case of eyes contact:	Flush eyes with plenty of clean running tap water for at least 15 minutes
Advice to doctor:	Treat symptomatically.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)



H.Q. : No.32,Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
 Tel : (60 7) 333 1222 Fax: (60 7) 332 0545 / 333 7919
 Branch : No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
 47100 Shah Alam, Selangor. Malaysia.
 Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
 Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal® BT-390 WINDSCREEN SEALANT

5. Fire Fighting Measures	
Flammability:	Very Low
Suitable extinguishing media:	Dry Chemical, Foam, CO ² , Water Fog
Flash Point	Minimum 180 °C

6. Accidental release measures	
Methods:	Exclude sources of ignition and ventilation the area Exclude non-essential personnel. Avoid breathing vapour

7. Handling and Storage	
Handling:	Ensure good ventilation during processing. Wear safety shoes.
Protection against fire/ explosion:	General rules of fire prevention should be observed.
Storage:	Keep in a cool shaded place, away from heat & direct sunlight.

8. Exposure control/ Personal protection	
Hand protection:	Suitable protective gloves.
Eye protection:	Safety / Protective Goggles

9. Physical and Chemical Properties	
Form:	Extruded solid putty tape
Specify gravity:	1.3 ± 0.1
Colour:	Black
Odour:	Odourless
Melting Temperature	Not Applicable
Boiling point:	Not Applicable
Flash point:	Minimum 180 °C
Freezing Point	Not Applicable
Ignition Temperature:	Non known
Vapour Pressure (25°C)	Non known
Soluble in Water (25°C)	Negligible, below 0-1%
Note: the above information is not intended for use in preparing specification.	



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)



H. Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
 Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
 Branch : No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
 47100 Shah Alam, Selangor. Malaysia.
 Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
 Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal® BT-390 WINDSCREEN SEALANT

10. Stability and Reactivity	
Hazardous Decomposition Products	Incomplete burning can produce CO, CO ² , and other harmful products.
Hazardous Reaction	No dangerous reaction known

11. Toxicological Information	
On the skin:	May cause sensitization
On the eye:	Possibility irritating

12. Ecological Information	
Large quantities of products should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface water.	

13. Disposal considerations	
Do not allow large quantities to enter the drains or watercourses or dispose of where ground surface may be affected. Residue in emptied containers should be covered and should be disposed of in accordance with regulations made under the control of Pollution & Environment Protection Acts.	

14. Transport Information	
Not Available	

15. Other Information	
These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.	

*** End Of MSDS ***