



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
Branch : No.43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor. Malaysia.
Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal® COLOSIL SEALANT

1. Product & Company Identification

1.1 Product Detail

Product name: Colosil Sealant
Physical form: Paste
Odour: Oxime Odour
Colour: White
CAS No.: Mixture

1.2 Company Details:

Manufacturer: Mohm Chemical Sdn Bhd
Address: No. 32 (Lot 1617), Jalan Temenggong, Off Jalan Tampoi, 81100
Johor Bahru, Johor, Malaysia.
Tel: + 60-7-3331222
Fax: + 60-7-3320545/ + 60-7-3337919

2. Composition/ Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Approx WT%</u>
Methyl Tri (Methylethylketoxime) Silane	22984-54-9	1.5%
Vinyl Tri(Methylethylketoxime) Silane	2224-33-1	1.5%
Treated Fume Silica	68583-49-3	10%
Dimethyl Siloxane	70131-67-8	87%

3. Hazards Identification

Ingestion: Irritation of the mouth, throat and stomach.
Skin contact: Uncured product contact will irritate lips, gums and tongue.
Uncured product contact may irritate the skin.
Inhalation: May cause mild respiratory irritation.
Eye contact: Uncured product contact irritates eyes.
Comments: Methyl Ethyl Ketoxime (MEKO) is formed upon contact with water or humid air. Male rodents exposed to MEKO vapour throughout their lifetime developed liver cancer. Additional testing is planned by the MEKO supplier to determine any relevance to humans. Until more data is known, exposure levels should be maintained as low as achievable



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)

MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.

Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919

Branch : No.43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor. Malaysia.

Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877

Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal® COLOSIL SEALANT

4. First-aid Measures

Take off all contaminated clothing immediately.

In case of ingestion: Seek medical advice immediately.

In case of skin contact: Wipe with paper towel and immediately clean with water and soap.

In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

5. Fire Fighting Measures

Suitable extinguishing media: All standard fire-fighting media.

Unsuitable extinguishing media: Unknown

Hazardous decomposition: Carbon dioxide, carbon monoxide, silicone dioxide and nitrogen oxides and formaldehyde.

6. Accidental release measures

Methods for cleaning up: Take up mechanically.

7. Handling and Storage

Handling: Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety shoes.

Protection against fire/ explosion: General rules of fire prevention should be observed.

Storage: Keep container tightly closed and dry.

Cautions: Extreme heavy in drum form if product packed in 200L drum.

8. Exposure control/ Personal protection

Ingredients with limited values to be controlled: Not indicated.

Local exhaust: Recommended

General ventilation: Recommended

Hand protection: Suitable protective gloves.

Eye protection: Safety/ protective glasses.

Flammability: Combustible

Note: Until more data is known, exposure levels should be maintained as low as achievable.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
Branch : No.43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor. Malaysia.
Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal® COLOSIL SEALANT

9. Physical and Chemical Properties

Form:	Paste
Specific gravity:	1.03
Colour:	Clear and pigmented
Viscosity:	Not indicated.
Odour:	Oxime.
%Volatile by volume (25°C):	= 3.0%
Total VOC:0	Less than 4%
Solubility in water:	Insoluble
Boiling point:	Not Applicable.
Flash point:	Not Applicable.
Ignition temperature:	Not Applicable.
Solubility in water(20°C):	Insoluble
Vapour pressure:	Not Applicable.
Solubility in organic solvent:	Toluene.

Note: the above information is not intended for use in preparing specification.

10. Stability and Reactivity

Chemical stability:	Stable
Incompatibility (material to be avoid):	None known.
Conditions to be avoid:	None known.
Dangerous reactions:	None known.
Dangerous products of decomposition:	Ketoxime during curing.
In case of fire, carbon dioxide, carbon monoxide, silicone dioxide and nitrogen oxides and formaldehyde.	

11. Toxicological Information

Acute toxicity:	Not determined
Primary irritant effect, On the skin:	Irritant for skin and mucous membranes.
On the eye:	Irritant effect
Sensitization:	Sensitization possible by inhalation.
Additional Toxicological information:	Until more data is known, exposure levels should be maintained as low as achievable.

12. Ecological Information

Complete information not yet available.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
Branch : No.43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor. Malaysia.
Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal® COLOSIL SEALANT

13. Disposal considerations

For cured sealant landfill may be suitable.
With respect to local regulation, dispose of to suitable incineration plant.

14. Transport Information

Proper shipping name: **Silicone Sealant**
Hazard technical name: **Not available.**
Hazard class: **Not available.**
No dangerous goods under the transport regulation.

15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of MSDS ***