



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)

MCX MARKETING SDN. BHD. (Co. No. 363532-T)

H.Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel: (60) 7 333 1222 Fax: (60) 7 332 0545/ 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
40400 Shah Alam, Selangor, Malaysia.

Tel: (60) 3 5124 0876/ 5124 0878 Fax: (60) 3 5124 0877

Email: info@mochem.com Website: www.mochem.com/ www.xtraseal.com

TECHNICAL DATA SHEET

xtraseal® BT-330 INSTANT FLASHING TAPE

DESCRIPTION:

xtraseal® BT-330 INSTANT FLASHING TAPE IS A BLACK, VERSATILE, SELF-ADHESIVE TAPE, COMPRISING AN ELSTOPLASTIC WEATHERPROOF BITUMEN COMPOUND COVERED BY A REINFORCES ALUMINIUM FILM. BITUMINOUS COMPOUND IS PROTECTED BY A SILICONIZED RELEASE FILM.

FEATURES:

- ◆ EASY TO APPLY
- ◆ WEATHERPROOF
- ◆ OUTSTANDING DURABILITY
- ◆ COST SAVING

USES:

- ◆ PROTECTION:
ASPHALT, BRICKWORK, CONCRETE, FIBER CEMENT SHEETS, METAL AND PLASTIC MATERIALS ON ROOFS AND COVERING IN GENERAL.
- ◆ SEALING & WATERPROOFING:
GLASS & PLASTIC WINDOW FRAMES, PARAPETS, SKYLIGHTS STRUCTURES, ETC.
- ◆ REPAIR WORK:
METAL AND FIBER CEMENT SHEETS ROOFING, SHINGLES, GUTTERS AND METAL TUBE.

APPLICATION:

- ◆ SURFACES MUST BE CLEAN, DUST-FREE AND DRY. RUST SHOULD BE REMOVED.
- ◆ CRACKS WIDER THAN 3MM SHOULD BE FILLED.
- ◆ REMOVE INSTANT FLASHING TAPE FROM THE RELEASE PAPER AND PRESS IT INTO POSITION USING FINGERTIP PRESSURE.
- ◆ USE A SEAM ROLLER TO SMOOTH OVER INSTANT FLASHING TAPE TO ENSURE GOOD CONTACT IS MADE.

PHYSICAL PROPERTIES:

SURFACE	PE COATED ALUMINIUM
ADHESIVE	BITUMINOUS COMPOUND
LINER	SILICONIZED FILM
THICKNESS	1.33M (0.052IN)
TOTAL THICKNESS	1.50MM (0.059IN)

WIDTH & LENGTH OF ROLL:

ROLL WIDTH	ROLL LENGTH
50MM	10 METERS (11 YARDS)
75MM	10 METERS (11 YARDS)
100MM	10 METERS (11 YARDS)



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)

MCX MARKETING SDN. BHD. (Co. No. 363532-T)

H.Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel: (60) 7 333 1222 Fax: (60) 7 332 0545/ 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
40400 Shah Alam, Selangor, Malaysia.

Tel: (60) 3 5124 0876/ 5124 0878 Fax: (60) 3 5124 0877

Email: info@mochem.com Website: www.mochem.com/ www.xtraseal.com

TECHNICAL DATA SHEET

xtraseal® BT-330 INSTANT FLASHING TAPE

SPECIFICATION:

TENSILE STRENGTH	65N
TEAR STRENGTH	18N/MM ²
ELONGATION	11%
SOFTENING POINT	+ 95°C
COLD FLEXIBILITY	>-40°C
ADHESION ON STEEL	5.8N/MM ²
UV RESISTANCE	GOOD
SERVICE TEMPERATURE	-40°C TO 80°C

STORAGE DETAILS AND SHELF LIFE:

ONE YEAR FROM DATE OF DISPATCH WHEN STORED AT 22°C (72°F) AND 50% RELATIVE HUMIDITY.

SHELF LIFE CAN VARY WITH TEMPERATURE AND HUMIDITY.

NOTE:

DO NOT APPLY INSTANT FLASHING TAPE IF SURFACE TEMPERATURE IS BELOW 5°C.
INSTANT FLASHING TAPE WILL BECOME BRITTLE IF ENCASED IN A CEMENTITIOUS MIX.
INSTANT FLASHING TAPE IS NOT RESISTANT TO ACID AND ALKALINE.