



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
Branch : No.43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor. Malaysia.
Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

TECHNICAL DATA SHEET

x'traseal[®] PS-200 PVC PIPE ADHESIVE

DESCRIPTION:

x'traseal[®] PS-200 PVC PIPE ADHESIVE is a premium grade, low viscosity clear color solvent based adhesive for PVC articles bonding applications. It is easy-to-apply, fast setting and extra strength formulation especially for waterproof bonding and coupling of rigid PVC, UPVC, and CPVC pipes and fittings, cable conduits, gutters, etc. It is safe for drinking water pipes upon complete curing.

PRODUCT SPECIFICATION & PROPERTIES:

APPEARANCE	Clear
PRINCIPAL COMPOSITION	Special PVC Resin
VISCOSITY	180 ± 20cps
SOLID CONTENT	15 ± 1%
SPECIFIC GRAVITY	0.88 ± 0.02
FLASH POINT	HIGHLY INFLAMMABLE

METHOD OF USE:

- ◆ Both surfaces to be bonded should be clean and dry.
- ◆ Apply the adhesive even to both surfaces.
- ◆ Join part together.
- ◆ Replace cap tightly after use. Store in a cool dry place.

STORAGE:

When the adhesive is kept in a well-sealed container and stored in a cool, dry place, a shelf life of the adhesive at least 12 months from date of dispatch can be reasonable expected.

CAUTION:

Avoid breathing in vapor. If in contact with eyes, flush with water for 15 minutes. If swallowed do not induce vomiting. Give a glass of water, and see deliberately inhaling vapours of this product can be harmful or total.

KEEP OUT OF REACH OF CHILDREN