



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)

MCX MARKETING SDN. BHD. (Co. No. 363532-T)

H.Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel: (60) 7 333 1222 Fax: (60) 7 332 0545/ 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
40400 Shah Alam, Selangor, Malaysia.

Tel: (60) 3 5124 0876/ 5124 0878 Fax: (60) 3 5124 0877

Email: info@mochem.com Website: www.mochem.com/ www.xtraseal.com

TECHNICAL DATA SHEET

x'traseal® PUTTY FILLER

DESCRIPTION:

x'traseal® PUTTY FILLER IS A READY TO USE FILLER FOR EXTERIOR AND INTERIOR. IT IS AN ACRYLIC BASED FORMULATION USED FOR BOTH BEDDING AND FINISHING TOGETHER WITH JOINT TAPE TO REINFORCE AND CONCEAL THE JOINTS, FASTENERS AND CORNER BEAD OF GYPSUMBOARD. IT CAN ALSO BE USE TO TEXTURE WALLBOARD SURFACES AND LAMINATE WALLBOARD TO AN EXISTING SURFACE SUCH AS OLD PLASTER, MASONRY OR GYPSUM WALLBOARD.

DUE TO ITS READY MIXED FORMULATION IT IS TIME SAVING WITH MINIMAL WASTAGE AND IS THUS HIGHLY ECONOMICAL AND CONVENIENT TO USE.

SUITABLE FOR:

CEMENT PLASTER, CONCRETE AND BRICK, EMULSION AND CEMENT PAINT ASBESTOS, CEMBOARD AND GYPSUMBOARD JOINT.

PRODUCT CHARACTERISTICS:

ADHESION	ADHERES FIRMLY TO ALL CLEAN, DRY AND GREASE FREE PLASTER AND WOOD SURFACES. WILL NOT CRACK OR FALL OUT WHEN DRY.
COLOUR	WHITE
DRYING TIME	A THIN FILM DRIES IN APPROX. 15 TO 30 MINUTES.
SANDABILITY	USE 150 GRIT SANDPAPER
ODOUR	ODOURLESS AFTER DRY
COVERAGE	30 TO 40 SQUARE FEET PER KG
SAFETY	NON-FLAMMABLE AND NON-TOXIC
CLEANING	CLEAN TOOLS WITH WATER
PACKING	0.5KG, 1.5KG, 5.0KG PAIL FORM 0.5KG CARTRIDGE FORM